

KD-RS2

Fully Automated Tissue Stainer



Features & Specifications

- ▶ 7-inch intelligent touch color screen, real-time display of working status, clear display.
- ▶ Supports dye name entry and viewing, and real-time status display, making data more intuitive.
- ▶ Working station synchronous displays and work progress is clear at a glance.
- ▶ Hot air intelligent control, automatic drying.
- ▶ Imported solenoid valve with intelligent control enables fully automatic water in/out for thorough cleaning.

- | | |
|--|---|
| ▶ Number of Cups: 18 (one for washout, one or drying) | ▶ Programmable: 20 sets |
| ▶ Capacity of Single Cup: 750ml | ▶ Programmable immersion sequence: 1~36 |
| ▶ Processing time per station: from 0~59 min 59 sec adjustable | ▶ Working Voltage: AC100V-120V/AC 220V-240V |
| ▶ Dripping Time: Adjustable within 0~30 s | ▶ Power: 50Hz /60Hz 500W |
| ▶ Temporary cleaning time: 0~59 seconds | ▶ Dimensions: 1380×420×470 mm |
| ▶ Number of slides processed at the same time: 50 slides | ▶ Weight: 75kg |

KD-RS3

Fully Automated Slide Stainer



Features & Specifications

- ▶ Intuitive touch screen and user-friendly interface ensure easy operation.
- ▶ Working station synchronous displays and work progress is clear at a glance.
- ▶ Password lock function is provided to ensure program security.
- ▶ Intelligent control of hot air, automatic drying.
- ▶ Intelligent water system with imported solenoid valve enables automatic intake and drainage for thorough cleaning.

- | | |
|---|---|
| ▶ Number of Cups: 15 (one for washing, one drying) | ▶ Programmable: 24 sets |
| ▶ Capacity of Single Cup: 350ml | ▶ Programmable immersion sequence: 1~30 |
| ▶ Processing time per station: 0~59 min 59 sec adjustable | ▶ Working Voltage: AC100V-120V/AC 220V-240V |
| ▶ Number of slides processed at the same time: 24 slides | ▶ Power: 50Hz /60Hz 400W |
| ▶ Agitating frequency: Adjustable within 0-6 times/minute | ▶ Dimensions: 980×295×340 mm |
| ▶ Dripping Time: Adjustable within 0-60s | ▶ Weight: 28kg |